



MT67 Sei
Mobile Computers

Features

Android 11 GMS.

The MT67 Sei runs on the Android 11 operating system with GMS. Packed with all the features and benefits of Android 11 OS, the MT67 Sei's 2.0Ghz octa-core processor in combination with the 4GB RAM can easily run multiple applications. The 64GB flash memory enables vast data to be stored offline, making the device a truly powerful data capture solution in the Newland range.

Style and comfort.

The MT67 Sei's design is well balanced in weight, and the soft curved edges add comfort to the user. The 4-inch capacitive full-colour touch screen displays high-quality sharp images and clear text. Featuring two scan triggers on each side of the device and a front power key, the MT67 Sei suits both left and right-handed operations for extra comfort.

Megapixel scanning.

The MT67 Sei has Newland Megapixel 2D scanning technology for

high-performance scanning of 1D and 2D barcodes, even if they are damaged or distorted. The laser aiming uses the Acuscan feature to ensure the user can decode barcodes even when they are displayed closely together.

Within 4 walls and beyond.

The dual-band Wi-Fi is the common wireless communication used in this device, but the 4G allows for roaming outside the network. The Bluetooth 5.0 is useful for pairing the device with peripherals like headsets, portable printers, or additional barcode scanners.

Device management & software tools.

The MT67 Sei comes fully equipped with Newland's free Ndevor MDM for managing all your devices from one location. SOTI, Airwatch, and 42 Gears are alternative MDM options for the MT67 Sei.



Suggested industries



Logistics



Retail



Transportation



Warehousing

MT67 Sei Technical specifications

Data Capture

1D	All major 1D symbologies
2D	All major 2D symbologies
Image Sensor	1280 x 800 CMOS
Illumination	White LED (625±10nm)
Aiming	Laser diode

Performance

Operating System	Android 11_GMS
Processor	2.0GHz octa-core 64-bit processor
Memory RAM	4GB
Memory Flash	64GB
Memory Storage Expansion (max.)	Micro SD/TF card (max. 128GB)

Physical

Dimensions (mm)	162(L) x 68(W) x 17(H) mm
Weight	250g (including battery)
Display	4" WVGA (800×480)
Touch Panel	Capacitive touch screen, Corning Gorilla glass
Keypad	24 keys (side keys included) with backlight + 3 virtual keys
Interfaces	USB Type-C, fast battery charging via USB
Battery Type	3.8V, 4800mAh
Expected Battery Life	10 hours
Expected Charge Time	3 hours
Notifications	Vibration, speaker and multi-color LEDs
Power Supply Input	AC110 ~ 240V, 50~60Hz
Power Supply Output	DC5/7/9V, 1.67A
Expansion Slot	Micro SD card (max. 128GB)
Camera	Front camera: 5 megapixels, fixed focus; Rear camera: 13 megapixels, auto focus, with LED flashlight
SIM	2 Nano SIM Card Slots (Nano+Nano or Nano+SD)

Environmental

Operating Temperature	-20°C to 55°C (-4°F to 122°F)
Storage Temperature	-30°C to 70°C (-22°F to 158°F)
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±15 kV (air discharge), ±8 kV (direct discharge)
Drop	1.5m drops to concrete
IP Rating	IP65

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

MT67 Sei Technical specifications

Wireless	
WWAN RADIO	2G: GSM: 850/900/1800/1900MHz; 3G: WCDMA (B1, B2, B5, B8), CDMA2000 1X/ EV-DO Rev. A (BC0), TD-SCDMA (B34, B39); 4G: TD-LTE (B34, B38, B39, B40, B41), FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)
WLAN RADIO	802.11 a/b/g/n/ac, compatible with 11 d/h/i/k/r/v/w, support 2.4GHz and 5GHz
WPAN RADIO	Bluetooth 5.0 LE, backward compatible
RFID	13.56MHz ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693
GPS	GPS (AGPS), GLONASS

Accessories	
Standard	USB cable, Battery, Multi-plug adapter, Wrist Strap, Rubber Boot
Optional	Charging Cradle, Battery, AC adapters, USB Cable, Pistol Grip, 4-slot Battery Charger, Wrist Lanyard, Rubber Boot

Software	
MDM (certified)	Ndevor, SOTI, Airwatch
Terminal Emulation (compatible)	Ivanti Velocity, StayLinked
Configuration Tools	Ndevor

Certifications	
Hardware	FCCID, RoHS, IEC62471, EN60950

Warranty	
Standard	2 years



OFERTĂ RAPIDĂ

Ai găsit echipamentul potrivit?

Trimite-ne cerințele tale și primești o recomandare configurată pentru aplicația, volumul și bugetul companiei.

OFERTA TA ÎN 3 PAȘI

01

Trimite-ne cerința

Produs, SKU, cantitate sau descrierea aplicației.

02

Verificăm configurația

Compatibilitate, accesorii, stoc și termen de livrare.

03

Primești rapid oferta

Configurație clară, preț și suport pentru decizie.



Scanează pentru cererea de ofertă

autoid.ro/contact

CERE OFERTĂ

08008 288 643

contact@autoid.ro

L-V 9:00 - 17:00